

Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: MICRO OPTICS
Colour: CAFFÈ
Dimming: PUSH, DALI
Emergency: NO
L: 868mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years

Tech data

Luminaire input power: 26.5W
Luminaire luminous flux: 2183lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 22W
Colour temperature: 3000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



COMPLETION ACCESSORIES



HERO: MOD.CIECO 250 CAF

108676.20



HERO: MOD.CIECO ANG.SX 150 CAF

108677.20



HERO: MOD.CIECO ANG.DX 150 CAF

108678.20



HERO: MOD.CIECO 1120 CAF

108679.20



HERO: MOD.CIECO 1400 CAF

108680.20



HERO: MOD.CIECO 1680 CAF

108681.20



HERO: COPPIA TESTATE CAF

108684.20

MOUNTING ACCESSORIES



HERO: SOSPL3000 1PZ. TESTA/CODA

108685.99



HERO: SOSPL3000 1PZ. UNIONE

108686.99



HERO: STAFFA PARETE "L" CAF

108687.20




HERO: KIT INCASSO LED (1X)

108688.99



HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99



KIT ALIMENTAZIONE L1200 5P BIA

108921.01





KIT ALIMENTAZIONE L1200 5P CAF

108921.20



KIT ALIMENTAZIONE L3000 5P BIA

108922.01



KIT ALIMENTAZIONE L3000 5P CAF

108922.20