

Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: SPOT
Beam: 14°
Colour: CAPPUCCINO
Dimming: PUSH, DALI
Emergency: NO
L: 1120mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years
Weight: 3.4kg

Tech data

Luminaire input power: 29W
Luminaire luminous flux: 2332lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 2X13W
Source luminous flux: 3040lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012


Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)




COMPLETION ACCESSORIES




HERO: MOD.CIECO 250 CAP

108676.21




HERO: MOD.CIECO ANG.SX 150 CAP

108677.21




HERO: MOD.CIECO ANG.DX 150 CAP

108678.21




HERO: MOD.CIECO 1120 CAP

108679.21




HERO: MOD.CIECO 1400 CAP

108680.21



HERO: MOD.CIECO 1680 CAP

108681.21



HERO: COPPIA TESTATE CAP

108684.21

MOUNTING ACCESSORIES



HERO: SOSP.L3000 1PZ. TESTA/CODA

108685.99



HERO: SOSP.L3000 1PZ. UNIONE

108686.99



HERO: STAFFA PARETE "L" CAP

108687.21




HERO: KIT INCASSO LED (1X)

108688.99




HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99




KIT ALIMENTAZIONE L1200 5P BIA

108921.01




KIT ALIMENTAZIONE L1200 5P CAP

108921.21



KIT ALIMENTAZIONE L3000 5P BIA

108922.01



KIT ALIMENTAZIONE L3000 5P CAP

108922.21