

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: MICRO OPTICS
Colour: BLACK
Dimming: PUSH, DALI
Emergency: NO
L: 868mm
A: 61mm
H: 68mm
Made in: ITALY
Warranty: 5 years

Tech data

Luminaire input power: 26.5W
Luminaire luminous flux: 2183lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 22W
Colour temperature: 3000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards


Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

HERO C


108845.02H

COMPLETION ACCESSORIES




HERO C: MOD.CIECO 250 NE

108852.02




HERO C: MOD.CIECO ANG.SX 150 NE

108853.02




HERO C: MOD.CIECO ANG.DX 150 NE

108854.02




HERO C: MOD.CIECO 1120 NE

108855.02



HERO C: MOD.CIECO 1400 NE

108856.02



HERO C: MOD.CIECO 1680 NE


108857.02



HERO C

108845.02H

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



HERO C: COPPIA TESTATE NE

108860.02



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 26/2/2024, 10:03:58