

## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD, CEILING MOUNTED  
Emission: DIRECT  
Optics: LENS UGR<19  
Colour: WHITE  
Dimming: PUSH, DALI  
Emergency: WITH ACCESSORY  
L: 595mm  
A: 595mm  
H: 35 (con driver)mm  
Warranty: 5 years  
Weight: 3kg

## Tech data

Luminaire input power: 34W  
Luminaire luminous flux: 4082lm  
Luminous flux in emergency: 1h: 14% / 3h: 5%  
IP: 40  
Insulation class: I  
Supply voltage: 850mA ALIMENT.INCLUSO  
UGR: <19  
SELV: Si

## Source

Light source: LED  
Source power: 30W  
Colour temperature: 4000K  
CRI: >90  
LED lifespan: 50000h L80 B20

## Compliance


CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.


[YALE: View more product info](#)

**MOUNTING ACCESSORIES**



BOX PER INST. PLAFONE THE PANEL 600X600

**102086.01**



THE PANEL 2: KIT INST.INC.RAS.CART.600


**102028.99**



SCHOOL: KIT ANTICADUTA L=3000


**104119.99**

**EMERGENCY ACCESSORIES**



THE PANEL 2: EMER.INC.3H 10/54VDC

**1020A5.99**



THE PANEL 2: EMER.INC.1H 10/54VDC

**1020A4.99**