

Features

Use: Indoor
Type of installation: RECESSED, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: BLACK
Dimming: WITH ACCESSORY
Emergency: NO
A: 40mm
H: 40mm
ø: 962mm
Made in: ITALY
Warranty: 5 years
Weight: 4.2kg

Tech data

Luminaire input power: 44.8W
Luminaire luminous flux: 2121lm
IP: 40
Insulation class: III
Supply voltage: MAX 1.8A
UGR: <19
SELV: No

Source

Light source: LED
Source power: 42W
Source luminous flux: 5932lm
Colour temperature: 3000K
CRI: >90
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[ARK: View more product info](#)

COMPLETION ACCESSORIES



ARK/HALOS: KIT GIUNZIONE PROFILI NE

109809.02

MOUNTING ACCESSORIES



HALOS: KIT 4 CAVI SOSPENSIONE L.3000

105159.99



HALOS: ROSONE ALIM. REMOTA NERO

105157.02




CAVO ALIMENTAZIONE L=3000 2X1 NERO

109001.02



HALOS: ROSONE DOPPIA ALIM. REMOTA NERO

105158.02



ARK: KIT INCASSO PER 962

109807.99

ELECTRICAL ACCESSORIES



HALOS: ROSONE-N DOPPIA ALIM ON/OFF NERO

105155.02



HALOS: ALIMENTATORE ON/OFF

105147.99



HALOS: ROSONE-N ALIM. ON/OFF NERO

105151.02

DIMMABLE ACCESSORIES



HALOS: ROSONE-N ALIM. DALI/PUSH NERO

105152.02



HALOS: ALIMENTATORE DALI/PUSH

105148.99



HALOS: ROSONE-N DOPPIA ALIM D/PUSH NERO

105156.02